

	PRCD 3016	PRCD 3000	PRCD 2000	PRCD 1509	PRCD 1509D	PRCD 500
Single/Dual Element	Single	Dual	Single	Single	Dual	Single
Maximum Tested (RPM)	200	200	200	200	200	200
Maximum Static Rating (PSI)	3,000	3,000	2,000	1,500	1,500	500
Maximum Dynamic Rating (PSI)	2,000	2,000	2,000	1,000	1,000	250
Pass Thru Diameter with Bearing (Inch)	7.0	7.0	7.0	9.0	9.0	8.2
Max Pass Thru Diameter without Bearing Inch	13.625	13.625	13.625	13.625	13.625	13.625
Height Range Installed in RCD Bowl (Inch)	50.1 to 59.8	65.1 to 74.7	50.1 to 59.8	47.8 to 55.2	66.1 to 73.4	Customizable
Recommended Applications	Managed Pressure Drilling (MPD) and high pressure	MPD and intermediate pressure		MPD and intermediate pressure applications that utilize larger drill pipe, smaller casing sizes, and/or other drill string components		Low pressure and surface drilling applications
Additional Features	API 16RCD Monogram	<ul style="list-style-type: none"> • Swivel Bottom Mount Flange Available • Multiple Outlet Sizes • Forged and Welded Bowl Options with Multiple Outlets • Pruitt Fluid Containment System (LP Bowls only) • HP Bowls are compatible with all PRCD Bearing Assemblies • Hydraulic Clamps with Check Valve System for Low Pressure and High Pressure applications 				